



SPECIFICATIONS

Current Rating: 1.5A AC,DC
 Voltage Rating: 50V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 100MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Material: NY6T
 Color: Natural(Black)

Circuit No.	Dimensions			
	A	B	C	D
02P	1.20	3.20	2.65	3.65
03P	2.40	3.40	3.85	4.85
04P	3.60	6.60	5.05	6.05
05P	4.80	7.80	6.25	7.25
06P	6.00	9.00	7.45	8.45
07P	7.20	10.2	8.65	9.65
10P	10.8	13.80	12.25	13.25

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	TITLE:
DRAWN	ZHIWEI.CHEN	2015.07.07	
CHECKED			
APPROVALS			PART NO. GP01-1200WRS-NP
TOLERANCES ARE			UNIT: mm
30~以上	±0.30	ANGLE	SCALE: 1:1
10~30	±0.20		PROJ:
5~10	±0.15	±2'	DRAWING NO.
~ 5	±0.10		SHEET 1 OF 1

深圳市联丰电子有限公司
 SHENZHEN LINFENG ELECTRONIC CO.,LTD