



Recommended PCB hole Layout
Top view (Tolerance±0.10)

- Specifications :
- Voltage rating: 125V AC / DC
 - Current rating: 1A AC / DC
 - Withstanding voltage: 500V AC/minute
 - Temperature range: -25°C~+85°C
 - Insulation resistance: ≥100MΩ
 - Contact resistance: ≤20mΩ
 - After environmental testing: ≤40mΩ

Poles	Dimensions(mm)			Poles	Dimensions(mm)		
	A	B	C		A	B	C
02	1.00	3.50	2.50	10	9.00	11.50	10.50
03	2.00	4.50	3.50	11	10.00	12.50	11.50
04	3.00	5.50	4.50	12	11.00	13.50	12.50
05	4.00	6.50	5.50	13	12.00	14.50	13.50
06	5.00	7.50	6.50	14	13.00	15.50	14.50
07	6.00	8.50	7.50	15	14.00	16.50	15.50
08	7.00	9.50	8.50	16	15.00	17.50	16.50
09	8.00	10.50	9.50				

APPROVALS		DATE	深圳市联丰电子有限公司 SHENZHEN LIANFENG ELECTRONIC CO.,LTD				
DRAWN	ZHIWEI.CHEN	2015.07.07	TITLE:	1.00mm Crimp Style Connector			
CHECKED			PART NO.	GP01-1002WRS-NP			
APPROVALS			SCALE:	1:1			
TOLERANCES ARE		30~以上 ±0.30	ANGLE	±2°			
		10~30 ±0.20	UNIT:	mm			
		5~10 ±0.15	DRAWING NO.				
		~ 5 ±0.10	PROJ:				
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	SHEET 1 OF 1