



PCB LAYOUT

SPECIFICATIONS
 Current Rating: 1A AC,DC
 Voltage Rating: 50V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 100MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Pin Material: Phosphor Bronze
 Solder Tabs: Brass
 Material: Nylon 6T,UL94V-0
 Color: Natural(Beige)

Circuit No.	Dimensions	
	A	B
2X05P	4.00	8.10
2X06P	5.00	9.10
2X08P	7.00	11.10
2X10P	9.00	13.10
2X15P	14.00	18.10
2X20P	19.00	23.10
2X25P	24.00	28.10

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	TITLE:		
DRAWN	ZHIWEI.CHEN	2015.07.07	1.00mm Crimp Style Connector		
CHECKED			PART NO. GP01-100IWRS-2xNP		
APPROVALS			UNIT: mm	SCALE: 1:1	PROJ:
TOLERANCES ARE					SHEET 1 OF 1
30~以上	±0.30	ANGLE	±2°		
10~30	±0.20				
5~10	±0.15				
~ 5	±0.10				

深圳市联丰电子有限公司
 SHENZHEN LINFENG ELECTRONIC CO.,LTD