



PIN数	DIM=A	DIM=B	DIM=C
40P	42.0	41.10	39.00
39P	41.0	40.10	38.00
38P	40.0	39.10	37.00
37P	39.0	38.10	36.00
36P	38.0	37.10	35.00
35P	37.0	36.10	34.00
34P	36.0	35.10	33.00
33P	35.0	34.10	32.00
32P	34.0	33.10	31.00
31P	33.0	32.10	30.00
30P	32.0	31.10	29.00
29P	31.0	30.10	28.00
28P	30.0	29.10	27.00
27P	29.0	28.10	26.00
26P	28.0	27.10	25.00
25P	27.0	26.10	24.00
24P	26.0	25.10	23.00
23P	25.0	24.10	22.00
22P	24.0	23.10	21.00
21P	23.0	22.10	20.00
20P	22.0	21.10	19.00
19P	21.0	20.10	18.00
18P	20.0	19.10	17.00
17P	19.0	18.10	16.00
16P	18.0	17.10	15.00
15P	17.0	16.10	14.00
14P	16.0	15.10	13.00
13P	15.0	14.10	12.00
12P	14.0	13.10	11.00
11P	13.0	12.10	10.00
10P	12.0	11.10	9.00
9P	11.0	10.10	8.00
8P	10.0	9.10	7.00
7P	9.0	8.10	6.00
6P	8.0	7.10	5.00
5P	7.0	6.10	4.00
4P	6.0	5.10	3.00

Electrical Characteristics:  
 Current rating: 0.5A AC/DC  
 Voltage rating: 50V AC/DC  
 Temperature range: -25°C~+85°C  
 Withstand Voltage: 500V AC/Minute  
 Contact Resistance: ≤ 30mΩ  
 Insulation resistance: ≥ 500MΩ

Material Description:  
 Contact: Phosphor Bronze Tin-Leadplated  
 Housing: LCP(UL94V-0)

ECN NO.	REV.	DATE.	DESCRIPTION.
	A		NEW
CHANGE.	CHECK.	APPRO.	

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	PART NO.	FPC 1.00mm Connector
CHECKED			UNIT: mm	SCALE: 1:1
APPROVALS			DRAWING NO.	PROJ:
TOLERANCES ARE				SHEET 1 OF 1
30~以上	±0.30	ANGLE		
10~30	±0.20			
5~10	±0.15			
~ 5	±0.10			

**深圳市联丰电子有限公司**  
 SHENZHEN LINFENG ELECTRONIC CO.,LTD