



PCB Layout Diagram
Top View

3	TERMINAL (-)	1	PHOSPHOR BRONZE, T=0.15MM	Sn-Plating
2	TERMINAL (+)	1	PHOSPHOR BRONZE, T=0.15MM	Sn-Plating
1	HOUSING	1	LCP	WHITE
NO	PAPT NAME	0' TY	MATPPIAI	PLATING & COP

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	深圳市联丰电子有限公司 SHENZHEN LINFENG ELECTRONIC CO.,LTD			
DRAWN	ZHIWEI.CHEN	2015.07.07	TITLE:	电池座 SMT	PART NO.	GP07-CR1632-01
CHECKED					SCALE:	1:1
APPROVALS					PROJ:	
TOLERANCES ARE		30~0.15	±0.30	ANGLE	UNIT:	mm
		10~30	±0.20		SCALE:	1:1
		5~10	±0.15		PROJ:	
		~ 5	±0.10	±2°	DRAWING NO.	
					SHEET	1 OF 1

NOTE:
 1. MATERIAL:
 a. HOUSING: THERMOPLASTIC GLASS FIBRE UL94V-0
 b. CONTACT: PHOSPHOR BRONZE
 (SURFACE PLATING: Sn100U")
 SEE ORDERING INFORMATION

2. ELECTRIC:
 a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
 b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
 c. DIELECTRIC VOLTAGE: 750V AC ONE SEC LEVEL
 d. OPERATING TEMPERATURE: -25° C ~ +85° C