



NOTE:

1. MATERIAL:

- a. HOUSING: THERMOPLASTIC GLASS FIBRE UL94V-0
- b. CONTACT: Mn Steel
- (SURFACE PLATING: Ni 100u")

SEE ORDERING INFORMATION

2. ELECTRIC:

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d. OPERATING TEMPERATURE: -25° C ~ +85° C

| | | | | |
|-----|--------------|------|--------------------|-----------------|
| 3 | TERMINAL (-) | 1 | Mn Steel, T=0.50MM | Ni-Plating |
| 2 | TERMINAL (+) | 1 | Mn Steel, T=0.50MM | Ni-Plating |
| 1 | HOUSING | 1 | PBT | BLACK |
| NO. | PART NAME | Q'TY | MATERIAL | PLATING & COLOR |

| | | | | | | |
|---------|------|-------|--------------|---------|--------|--------|
| ECN NO. | REV. | DATE. | DESCRIPTION. | CHANGE. | CHECK. | APPRO. |
| | A | | NEW | | | |

| | | | | | | |
|----------------|-------------|-------------|-------------------------|-------------|------------|--------------|
| APPROVALS | | DATE | TITLE: | | | |
| DRAWN | ZHIWEI.CHEN | 2015.07.07 | 电池座 | | | |
| CHECKED | | | PART NO. GP07-CR2430-01 | | | |
| APPROVALS | | | SCALE: 1:1 | | | |
| TOLERANCES ARE | | 30~以上 ±0.30 | ANGLE | UNIT: mm | SCALE: 1:1 | PROJ. |
| | | 10~30 ±0.20 | | | | |
| | | 5~10 ±0.15 | | | | |
| | | ~ 5 ±0.10 | ±2' | DRAWING NO. | | SHEET 1 OF 1 |



深圳市联丰电子有限公司
SHENZHEN LINFENG ELECTRONIC CO.,LTD