



PCB Layout Diagram
Top View

3	TERMINAL (-)	1	Mn Steel, T=0.60MM	Ni-Plating
2	TERMINAL (+)	1	Mn Steel, T=0.60MM	Ni-Plating
1	HOUSING	1	PBT	BLACK
NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	TITLE:			
DRAWN	ZHIWEI.CHEN	2015.07.07	PART NO. GP07-CR2032-09			
CHECKED			SHENZHEN LINFENYING ELECTRONIC CO.,LTD			
APPROVALS			SHENZHEN LINFENYING ELECTRONIC CO.,LTD			
TOLERANCES ARE		30~以上	±0.30	ANGLE	UNIT: mm	SCALE: 1:1
		10~30	±0.20			PROJ.
		5~10	±0.15	±2'	DRAWING NO.	
		~ 5	±0.10			SHEET 1 OF 1

NOTE:

1. MATERIAL:

- a. HOUSING: THERMOPLASTIC GLASS FIBRE UL94V-0
- b. CONTACT: Mn Steel
- (SURFACE PLATING: Ni100u")

SEE ORDERING INFORMATION

2. ELECTRIC:

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d. OPERATING TEMPERATURE: -25° C ~ +85° C



深圳市联丰电子有限公司
SHENZHEN LINFENYING ELECTRONIC CO.,LTD

电池座