



NOTE:

1. MATERIAL:

- a. HOUSING: PA6T WHITE
- b. CONTACT: PHOSPHOR BRONZE (SURFACE PLATING: Au*U")

SEE ORDERING INFORMATION

2. ELECTRIC:

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d. OPERATING TEMPERATURE: -25° C ~ +85° C

ECN NO.	REV.	DATE.	DESCRIPTION.
	A		NEW
CHANGE.	CHECK.	APPRO.	

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	PART NO.	GP07-CR2032-19
CHECKED			UNIT: mm	SCALE: 1:1
APPROVALS			DRAWING NO.	PROJ:
TOLERANCES ARE		ANGLE		SHEET 1 OF 1
30~0.15	±0.30	±2°		
10~30	±0.20			
5~10	±0.15			
~ 5	±0.10			

深圳市联丰电子有限公司
SHENZHEN LINFENG ELECTRONIC CO.,LTD