



PCB Layout Diagram  
Top View

**NOTE:**

**1. MATERIAL:**

- a. HOUSING: THERMOPLASTIC GLASS FIBRE UL94V-0
- b. CONTACT: Mn Steel
- (SURFACE PLATING: Ni100u")

SEE ORDERING INFORMATION

**2. ELECTRIC:**

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d. OPERATING TEMPERATURE: -25° C ~ +85° C

3	TERMINAL (-)	1	Mn Steel, T=0.50MM
2	TERMINAL (+)	1	Mn Steel, T=0.50MM
1	HOUSING	1	PBT
NO.	PART NAME	Q' TY	MATERIAL

<b>APPROVALS</b>		<b>DATE</b>	<p><b>深圳市联丰电子有限公司</b> SHENZHEN LINFENG ELECTRONIC CO.,LTD</p>
<b>DRAWN</b>	ZHIWEI.CHEN	2015.07.07	
<b>CHECKED</b>			
<b>APPROVALS</b>			<b>TITLE:</b>

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.																												
	A		NEW																															
<table border="1"> <tr> <td><b>TOLERANCES ARE</b></td> <td>30~以上</td> <td>±0.30</td> <td><b>ANGLE</b></td> <td></td> <td><b>PART NO.</b></td> <td>GP07-CR2477-02</td> </tr> <tr> <td></td> <td>10~30</td> <td>±0.20</td> <td></td> <td></td> <td><b>UNIT:</b></td> <td>mm</td> </tr> <tr> <td></td> <td>5~10</td> <td>±0.15</td> <td></td> <td></td> <td><b>SCALE:</b></td> <td>1:1</td> </tr> <tr> <td></td> <td>~ 5</td> <td>±0.10</td> <td>±2'</td> <td></td> <td><b>DRAWING NO.</b></td> <td></td> </tr> </table>							<b>TOLERANCES ARE</b>	30~以上	±0.30	<b>ANGLE</b>		<b>PART NO.</b>	GP07-CR2477-02		10~30	±0.20			<b>UNIT:</b>	mm		5~10	±0.15			<b>SCALE:</b>	1:1		~ 5	±0.10	±2'		<b>DRAWING NO.</b>	
<b>TOLERANCES ARE</b>	30~以上	±0.30	<b>ANGLE</b>		<b>PART NO.</b>	GP07-CR2477-02																												
	10~30	±0.20			<b>UNIT:</b>	mm																												
	5~10	±0.15			<b>SCALE:</b>	1:1																												
	~ 5	±0.10	±2'		<b>DRAWING NO.</b>																													

**深圳市联丰电子有限公司**  
SHENZHEN LINFENG ELECTRONIC CO.,LTD

**电池座**

GP07-CR2477-02

SCALE: 1:1

PROJ:

SHEET 1 OF 1